

> PRINT

FS-9130DN

A3 BLACK AND WHITE PRINTER

READY TO TAKE CARE OF ANY WORKLOAD



- > Up to 40 pages per minute in A4, 23 pages per minute in A3
- > 64MB memory standard, upgradeable to 576MB
- > Duplex unit for double-side printing as standard
- > PDF direct printing from USB Flash Memory devices
- > Wide range of paper options
- > Long-life components and easy maintenance
- > Network connectivity as standard

With a print speed of 40 pages per minute in A4, the KYOCERA FS-9130DN is ready to carry you through the heaviest of loads without slowing down. Fast, efficient and reliable, this printer also has a highly functional modular design. The paper input and finishing options make it easy to fit the printer to your teams precise needs.



ECOSYS stands for ECOlogy, ECONomy and SYStem printing. With their long-life components, ECOSYS devices are designed to maximise durability and minimise the total cost of ownership with regard to maintenance, administration and consumables. The cartridge-free system means that the toner is the only consumable and hardly ever needs to be replaced. The modular design concept allows you to add workflow-enhancing functions as required and the integrated system software provides long-term cross-network compatibility.

GENERAL

Technology: KYOCERA ECOSYS, Laser

Engine speed: Max. 40/23 pages per minute A4/A3 simplex, max. 33/16 pages (16/8 sheets) per minute A4/A3 duplex

Resolution: 1,200 dpi quality (1,800 x 600)

Time to first page: 3.5 seconds

Warm-up time: 60 seconds from power on

Duty cycle: Max. 200,000 pages per month, max. average 20,000 pages per month

Power source: AC 220 ~ 240 V, 50/60 Hz

Power consumption: Printing: 710 W, Stand-by: 160 W, Power-Saving (ECOpower): 4.5 W

Noise (ISO 7779): Printing: 51 dB(A), Stand-by: 37 dB(A), Power-Saving (ECOpower): Immeasurably low

Dimensions (W x D x H): 599 x 646 x 615 mm

Weight: Main unit: Approx. 68 kg

Certifications: TÜV/GS, CE, PTS

This product is manufactured according to ISO 9001 quality standard and ISO 14001 environmental standard.

PAPER HANDLING

All mentioned paper quoted are based on a paper thickness of max. 0.11 mm. Please use paper recommended by KYOCERA under normal environmental condition.

Input capacity: 2 x 500-sheet universal paper cassette, 60-105g/m², A3, A4, A4R, A5R, B4, B5, B5R, Letter, Letter-R, Legal, Ledger, Folio, STMT

200-sheet multi-purpose cassette, 45-200g/m², A3-A6R, Custom (88 x 148 mm to 297 x 450 mm)

Max. input capacity with optional paper feeder PF-750: 4,200 sheets

Duplex as standard supports A3, A4, A4R, A5R, B4, B5, B5R, Letter, Letter-R, Legal, Ledger, 60-80g/m²

Output capacity: 500 sheets face-down

CONTROLLER

Processor: PowerPC 750FL / 600MHz

Memory: Standard 64MB + EComemory, max. 576MB (1 DIMM slot)

Emulations: PCL6/PCL5e incl. PjL, PostScript 3TM (KPD L 3), KC-GL (HP-7550A), PDF direct printing, automatic emulation sensing (AES), Line Printer, IBM Proprinter X24E, Epson LQ-850, Diablo 630

Controller language: PRESCRIBE IIe

Fonts: 80 outline fonts (PCL), 136 PostScript Fonts, 1 bitmap font, 45 types of one-dimensional barcodes plus two-dimensional barcode PDF-417
Downloadable fonts: Kyocera, PCL + TrueType format, Type 1 + 3 format

Print features: eMPS – job management functionality with optional hard disk HD-5 for quick copy, proof and hold, private print and job storage 100 department codes for Accounting, PDF direct printing via USB Flash memory device, professional finishing capabilities

INTERFACE

Standard interface: Fast Ethernet 10/100Base-TX, High speed bi-directional parallel (IEEE 1284), USB 2.0 (Hi-Speed), USB Host Interface dedicated for USB Flash Memory device, KU10-LV option interface slot

Multiple interface connection (MIC): Allows simultaneous data transfer via up to four interfaces, with each interface having its own virtual printer.

OPTIONS

Paper handling

PF-700 Paper feeder: 2 x 500 sheets, 60-105g/m², A3, A4, A4R, A5R, B4, B5, B5R, Letter, Letter-R, Legal, Ledger, Folio, STMT

PF-750 Paper feeder: Max. 3,000 sheets, 60-105g/m², A4, B5, Letter

DF-710 Document finisher + AK-705*:

Main tray: Max. 3,000 sheets A4 or 1,500 sheets A3

face-down, 60-200g/m², A3-B5,

Sub tray left: Max. 200 sheets A4 or 100 sheets A3/B4

face-up, 45-200g/m², A3-A6R,

Sub tray right: Max. 50 sheets A4 face-up, 45-200g/m²,

A4-A6R,

Stapling: Max. 50 sheets A4 or 30 sheets A3, stapling at 3 positions

BF-710 Booklet unit for DF-710: Max. 64 pages (16 sheets) booklet folding and stapling, 60-80 g/m², cover sheet 60-200g/m², A3, B4, A4R

PH-5C/PH-5D Punch unit for DF-710: A3-A5R, 45-200g/m², 2-hole/4-hole/Swedish type

MT-710 Mailbox for DF-710: 7 bins, 60-80g/m², A3-A5R, 7 bins x 100 sheets A4 or 50 sheets A3/B4

DF-730 Document finisher + AK-705*: Max. 1,000 sheets A4 or 500 sheets A3/B4, 64-128g/m², A3-B5, one position stapling max. 30 sheets A4 or 20 sheets A3/B4, 64-80g/m²

CB-700 Cabinet (W x D x H): wooden desk with storage capacity

CB-710 Cabinet (W x D x H): metal desk with storage capacity

*Adapter-Kit AK-705 is required for the use of DF-710/DF-730 document finisher.

The use of the hard disk HD-5 or extended RAM-Disk size is highly recommended to achieve full document finisher functionality.

Memory

Printer memory: 1 DDR SDRAM DIMM slot (64, 128, 256 or 512MB)

CompactFlash® card: 1 slot (up to 2GB), forms, fonts, logos, macro storage

HD-5 Hard disk: 40GB, storage of data, forms, fonts and job management

Data security kit C: Overwrite and encryption of HD-5 USB Flash Memory; Supports PDF direct printing via USB Host Interface

Optional interface

IB-23 Network card: 10Base-T/100BaseTX

IB-11 Serial interface: RS-232C serial interface

PS159: Wireless LAN (802.11b/g)

PS1109 Gigabit Ethernet: 10BaseT/100BaseTX/1000BaseSX (SC)

PS1129 Gigabit Fibre Optic: 1000BaseSX (SC)

CONSUMABLES

TK-710 Toner-kit: Microfine toner for 40,000 pages in accordance with ISO/IEC 19752

Capacity of starter toner is 20,000 pages in accordance with ISO/IEC 19752

MAINTENANCE

MK-710 Maintenance-kit: 500,000 pages

WARRANTY

2-year warranty as standard. KYOCERA guarantees the drum and developer for 3-year's or 500,000 pages (whichever occurs sooner), provided each printer is used and cleaned in accordance with the service instructions.



The up to 5-year on-site warranty extension for printer and options. The warranty is limited to 2 million pages (3 million pages with KYOLife).

KYOCERA Document Solutions (UK) Ltd
Eldon Court, 75-77 London Road, Reading RG1 5BS
Tel: 0118 931 1500 – Fax: 0118 931 1108
www.kyoceradocumentsolutions.co.uk – info@duk.kyocera.com

KYOCERA Document Solutions does not warrant that any specifications mentioned will be error-free. Specifications are subject to change without notice. Information is correct at time of going to press. All other brand and product names may be registered trademarks or trademarks of their respective holders and are hereby acknowledged.

* Depending on the country

YOUR KYOCERA BUSINESS PARTNER

 **KYOCERA**
Document Solutions