

> PRINT > COPY > SCAN > FAX

ECOSYS M3040idn ECOSYS M3540idn

A4 BLACK AND WHITE MULTIFUNCTIONALS





- > Up to 40 A4 pages per minute
- > Double-sided print, copy, fax* and colour scan functionality
- > 75-sheet reversing document processor supporting A6 originals
- > Mobile printing support including AirPrint
- > 7-inch full-colour touch panel with home screen provides ease of use
- > HyPAS[™] solution platform enables powerful customisation

*ECOSYS M3540idn only

For workgroups who demand a compact, flexible and easy to use multifunctional device, the ECOSYS M3040idn and ECOSYS 3540idn offer the ideal solution. Both models have been designed to maximise efficiency of document throughput whilst minimising user time. Thanks to their full colour touch screen operation panel and integrated HyPASTM platform, users can customise these devices to suit their specific needs. With output speeds of 40 pages per minute users need also not compromise on workflow efficiency. Add to this, long-life components that provide exceptional reliability and low running costs which minimise the impact on the environment, these devices really do offer an unbeatable package.



ECOSYS® ECOSYS stands for ECOlogy, ECOnomy and SYStem printing. With their long-life components, ECOSYS devices are designed to maximise durability and minimise the total cost of ownership with regard to maintenance, administration and consumables. The cartridge-free system means that only the toner has to be replaced regularly. The modular design concept allows you to add workflow-enhancing functions as required. Integrated system software provides long-term cross-network compatibility.

ECOSYS M3040idn | ECOSYS M3540idn

Technology: KYOCERA ECOSYS Laser. HvPAS™ Solution Platform

Control panel display: 7-inch full-colour touch panel display, tilt in 3 steps (0, 10, 20 degree)

Engine speed: Up to 40 pages A4 per minute Resolution: 1,200 dpi quality (1,800 x 600, print),

600 x 600 dpi, 256 greyscales (scan / copy)

Duty cycle:

Maximum. 150,000 pages per month Maximum average. 15,000 pages per month Average. 4,000 pages per month Warm-up time: Approx. 21 seconds or less

Time to first print / copy: Approx. 9 seconds or less

CPU: PowerPC 465S / 667 MHz

Memory: Standard 1,024 MB, max. 2,048 MB

Standard interface: USB 2.0 (Hi-Speed), 2 x USB Host 2.0, GigaBit Ethernet (10BaseT / 100Base-TX / 1000BaseT), slot for optional internal interface or SSD hard disc, slot for optional SD / SDHC® card

Integrated accounting: 100 department codes Dimensions (W x D x H): 475 x 455 x 575 mm

Weight: Approx. 22 kg

Power source: AC 220 ~ 240 V, 50 / 60 Hz

Power consumption

EC	OSYS M3040idn	ECOSYS M3540idn
Copying / Printing:	684 W	685 W
Ready mode:	60.6 W	61.6 W
Low-power mode:	35.3 W	36.3 W
Sleep-mode:	2.4 W	2.4 W

Noise (Sound pressure level): ISO 7779 / ISO 9296):

ECOSYS M3040idn ECOSYS M3540idn 27.8 dB (A) LpA 27.3 dB (A) LpA Ready mode: Copying / Printing: 51.5 dB (A) LpA 51.5 dB (A) LpA Quiet mode: 47.9 dB (A) LpA 48.6 dB (A) LpA

Typical Electricity Consumption (TEC): 2.3 KWh / week

Safety standards: TÜV / GS, CE

This unit is manufactured according to ISO 9001 quality standard and ISO 14001 environmental standard.

All paper capacities quoted are based on a paper thickness of max. 0.11 mm. Please use paper recommended by KYOCERA under normal environmental conditions

Input capacity: 100-sheet multi-purpose tray; 60 - 220 g/m²; A4, A5, A6, B5, Letter, Legal, Custom (70 x 148 - 216 x 356) mm) 500-sheet universal paper cassette, 60-120 g/m²; A4, A5, B5, Letter, Legal, Custom (140 x 210 - 216 x 356 mm) Max. input capacity incl. options: 2,600 sheets

Duplex unit: Duplex as standard supports A4, A5, B5, Letter, Legal, Custom (140 x 210 mm - 216 x 356 mm),

Reversing document processor: 75-sheet, 50-120 g/m², A5, A6, B5, Letter, Legal, Custom (105 x 148 to 216 x 356 mm)

Output capacity: 250-sheet-face-down with paper full

PRINT FUNCTIONS

Controller language: PRESCRIBE IIe

Emulations: PCL 6 (5c/XL), KPDL 3 (PostScript 3-compatible), Line Printer, IBM Proprinter X24E, Epson LQ-850, PDF Direct Print 1.7, XPS Direct Print

Operating systems: All current Windows operating systems, MAC OS X version 10.5 or higher, Unix, Linux as well as other operating systems on request

Fonts / barcodes: 93 outline fonts (PCL 6, KPDL 3) + 8 (Windows Vista), 1 bitmap font, 45 types of one-dimensional barcodes, 1 type of two-dimensional barcode (PDF417)

Features: AirPrint, Encrypted PDF Direct Print, IPP printing, Email printing, WSD print, Secure printing via SSL, IPsec, HTTPS, SNMPv3, IPPS, POP over SSL, SMTP over SSL. Private Print, Toner save mode

COPY FUNCTIONS

Max. original size: A4 / Legal Continuous copying: 1-999

Zoom range: 25 - 400 % in 1% steps

Preset magnification ratios: 7 reductions / 5 enlargements

Exposure mode: Auto, manual: 9 steps

Image adjustments: Text + photo, text, photo, graphic/map

Features: Scan-once-copy-many, electronic sort, 2in1, 4in1, ID-card copy, job reserve, priority print, program, auto duplex copy, split copy, continuous scan, auto cassette change, copy density control

SCAN FUNCTIONS

Functionality: Scan-to-e-mail, Scan-to-FTP, Scan-to-SMB, Scan to USB Host, Network Twain, WSD (WIA) scan (USB,

Scan speed: 40 ipm (300 dpi, A4, black and white), 30 ipm (600 dpi, A4, black and white, 300 dpi, A4, colour)

Scan resolution: 600, 400, 300, 200 dpi (256 greyscales)

Max. scan size: A4, Legal

Original recognition: Text, photo, text + photo, for OCR File types: PDF (high compression, encrypted, PDF/A), JPEG, TIFF, XPS

Compression method: MMR/JPEG

Features: Colour scan, integrated address book, Active Directory support, encrypted data transfer, multi-send (e-mail, fax, SMB / FTP folder, print) at once

FAX FUNCTIONS (ECOSYS M3540idn only)

Compatibility: ITU-T Super G3 Modem speed: Max. 33.6 kbps

Transmission speed: Less than 3 seconds

Scanning speed: 2.5 seconds One-touch dial: 100 numbers Address book: 200 entries

Scanning density

Normal: 200 x 100 dpi Fine: 200 x 200 dpi Superfine: 200 x 400 dpi Ultrafine: 400 x 400 dpi Halftone: 256 greyscales

Maximum original size: A4. Legal Compression method: IBIG, MMR, MR, MH Memory reception: 256 sheets or more

Features: Network fax, duplex transmission and reception, encrypted transmission and reception, polling transmission and reception, broadcast

Paper handling

PF-320 Paper feeder (max. 4 units): Max. 500 sheets; 60-120 g/m2; A4, A5, B5, Letter, Legal, Custom (148 x 210 mm - 216 x 356 mm)

Memory upgrade MDDR3-1GB: 1,024 MB

HD-6 SSD hard disc: 32 GB for easy document management HD-7 SSD hard disc: 128 GB for easy document management

Data security kit (E): in line with security level EAL3

UG-33: ThinPrint support

USB IC Card Reader + Card Authentication Kit (B) Support for various authentication keys available

IC Card Reader Holder 10

To integrate the USB IC Card Reader

Optional interfaces

IB-50 Gigabit Ethernet: 10BaseT / 100BaseTX / 1000BaseT

IB-51 Wireless LAN: 802.11b / g / n

CB-360 Cabinet: Wooden desk with storage capacity

CONSUMABLES

Average continuous toner yield in accordance with ISO / IEC 19752

TK-3150 Toner-Kit: Microfine toner for 14,500 pages A4 Capacity of starter toner is 6,000 pages A4

2-year warranty* as standard. Kyocera guarantees the drum and developer for 3 years or 300,000 pages (whichever occurs sooner), provided each device is used and cleaned in accordance with the service instructions



Lip to 5-year on-site warranty extensions available for printer and options.







KYOCERA Document Solutions (UK) Ltd, Eldon Court, 75-77 London Road, Reading RG15BS Tel: 0118 931 1500 - Fax: 0118 931 1108 www.kyoceradocumentsolutions.co.uk – info@duk.kyocera.com

KYOCERA Document Solutions does not warrant that any specifications mentioned will be error-free. Specifications are subject to change without notice. Information is correct at time of going to press. All other brand and product names may be registered trademarks or trademarks of their respective holders and are hereby acknowledged.

*Depending on the country

