

> PRINT > COPY > SCAN > FAX

TASKalfa 9002i

A3 BLACK AND WHITE MULTIFUNCTIONAL

HIGH PRODUCTIVITY MATCHED WITH HIGH **PERFORMANCE**



Up to 90 pages per minute black and white.

1200x1200 dpi print resolution (2 bit depth*).

Individual paper handling options, including booklet and tri-folding.

Standard network and optional NFC mobile printing, as well document scanning.

.....















The TASKalfa 9002i sets new levels of high speed printing for light production environments. With high speed comes high productivity. With a maximum paper input capacity of 7,650 sheets and maximum output capacity of 4,300 sheets this device deals with large print jobs effortlessly and efficiently. A fast processor and large memory ensures print jobs are processed at high speed whilst the optional finisher can deliver completed booklets and tri-folded leaflets in-house. The 9" full colour touch screen also allows operators to quickly and intuitively access the myriad of time saving functions available from this device.



The TASKalfa 9002i incorporates extremely durable components that guarantee efficient and reliable operation, to meet the demanding requirements of busy office environments. The TASKalfa 9002i provides effective productivity and maximum flexibility whilst ensuring minimum impact on the environment.

Technology: KYOCERA Laser Monochrome, HyPAS™ solution platform

Solution platform
Engine speed (pages per minute): Up to 90/45 ppm A4/A3
Resolution: 1,200 x 1,200 dpi, 2-bit depth for print quality
of 4,800 dpi equivalent x 1,200 dpi
Warm-up time from power on: Approx. 30 seconds or less
Time to first page: Approx. 3.6 seconds or less
CPU: Freescale QorlQ T1024 Dual Core 1.4GHz
Memory: 4.5 GB RAM + 8 GB SSD + 320 GB HDD
Standard interfaces: USB 2.0 (His Speed USB). USB Host x

Standard interfaces: USB 2.0 (Hi-Speed USB), USB Host x 4, Fast Ethernet 10BaseT/100BaseTX/1000BaseT, slot for optional print server, slot for optional SD, SDHC card, slot

Optional print server, sacrot optionates, some case for optional fax system

Dimensions (W x D x H) – main unit
750 x 822 x 1234mm (DP, operation panel included)

Weight: Main unit approx. 150 kg

Power source: AC 220 V ~ 240 V, 50/60 Hz

Power consumption Printing: 1,340 W Ready mode: 100 W

Sleep mode: 1 W or less Noise (sound pressure level ISO 7779/ISO 9296) Printing: 75 dB(A) LpA

Ready mode: 58 dB(A) LpA
Safety standards: 65, TÜV, CE; This unit is manufactured
according to ISO 9001 quality standard and ISO 14001
environmental standard. RoHS compatibility

PAPER HANDLING

All paper capacities quoted are based on paper thickness

All paper capacities quoted are based on paper thickness of max. 0.11 mm. Please use paper recommended by KYOCERA under normal environmental conditions.

Input capacity: 150-sheet multi-purpose tray, 60 – 300 g/m² (banner 136 – 165 g/m²), A6R – 305 x 457 mm, banner max. 305 x 1,220 mm; 2x 1,500-sheet high-capacity paper deck, 60 – 256 g/m², A4, B5; 2x 500-sheet universal paper cassette, 60 – 256 g/m², A4, B5; 2x 500-sheet universal paper cassette, 60 – 256 g/m², Capacity with options: 7,650 sheets A4 Document processor: (one-path duplex scanning) 270 sheets; 35 – 220 g/m² (simplex), 50 – 220 g/m² (duplex); A6R – Banner up to 2.200 mm

- Banner up to 2,200 mm Duplex unit: Duplex as standard supports A5R – 305 x 457 mm, 60 – 256 g/m² Output capacity

(D): upper 100 sheets, lower 250 sheets; max. optional output capacity 4,300 sheets

PRINT FUNCTIONS
Controller language: PRESCRIBE
Emulations: PCL6 (PCL5c / PCL-XL), KPDL3 (PostScript 3
compatible), PDF Direct Print, XPS Direct Print and OpenXPS

Operating systems: All current Windows operating systems, Mac OS X Version 10.8 or higher, UNIX, LINUX, as well as other operating systems on request.

as well as other operating systems on request.

Fonts/barcodes: 93 outline fonts (PCL), 136 fonts (KPDL3),
8 fonts (Windows Vista), 1 Bitmap font, 45 types of onedimensional barcodes plus two-dimensional barcode (PDF-417)

Print features: Encrypted PDF Direct Print, IPP printing,
e-mail printing, WSD print, secure printing via SSL, IPsec,
SNMPv3, quick copy, proof and hold, Private Print, job
storage and job management functionality

Mobile printing support: KYOCFRA Mobile Print and for IOS

Mobile printing support: KYOCERA Mobile Print app for iOS and Android, AirPrint, Mopria, NFC, Direct Wi-Fi, Google Cloud Print

COPY FUNCTIONS
Max. original size: A3

Continuous copying: 1 – 9999
Zoom range: 25 – 400% in 1% steps
Preset magnification ratios: 5R/5E
Digital features: Scan once copy many, electronic sort, 2-in-

1 and 4-in-1 function, image repeat copy, page numbering, cover mode, booklet copy, interrupt copy, form overlay, stamp function and skip-blank-page function.

Exposure mode: Auto, manual: 16 steps Image adjustments: Text + photo, text, photo, map

SCAN FUNCTIONS

Functionality: Scan-to-email, Scan-to-FTP, Scan-to-SMB, Scan-to-USB Host, Scan-to-box, Network TWAIN, WSD scan Scan speed: (A4, 300 dpi, Dual Scan) 220 images per minute Scan resolution: 600 x 600 dpi, 400 x 400 dpi, 300 x 300 dpi, 200 x 400 dpi, 200 x 200 dpi, 200 x 100 dpi (24 bit) Max. scan size: A3, Banner up to 2.200 mm Original recognition: Text, photo, text + photo, optimised

File types: PDF (high compression, encrypted, PDF/A), Searchable PDF (OCR), JPEG, TIFF, XPS, OpenXPS

FAX FUNCTIONS (OPTIONAL)
Compatibility: ITU-T Super G3
Modem speed: Max. 33.6 kbps
Transmission speed: Max. 3 seconds (JBIG)
Fax resolution:

Normal: 200 x 100 dpi Fine: 200 x 200 dpi Superfine: 200 x 400 dpi Ultrafine: 400 x 400 dpi

Maximum original size: A3, Banner up to 1,600 mm Compression method: JBIG, MMR, MR, MH Features: Opt. Internet-fax, network faxing, rotate transmission, rotate reception, duplex fax reception, memory reception, mailbox, remote diagnostics, dual fax with second fax system 12

TK-6725 Toner-Kit: Average continuous toner yield 70,000 pages in accordance with 6% coverage A4
WT-861 Waste Toner Bottle

600,000 sheets (in accordance with 6% coverage)

Staple cartridge: SH-10 for BF-730, SH-12 for DF-7110

OPTIONS

Fax System 12 Internet Fax Kit (A) Paper handling PF-730(B) Paper feeder

2x 500 sheets, 60 – 256 g/m², A5R – 305 x 457 mm, folio **PF-740(B) Paper feeder** 2x 1,500 sheets, 60 – 256 g/m², A4, B5, letter **PF-7130 Paper feeder**

PF-730 Paper feeder 500 sheets, 60 – 256 g/m², A5R – 305 x 457 mm PF-7320 A4 side deck: 3,000 sheets, 60 – 256 g/m², A4, B5 DF-7110 Document finisher Main tray: max. 4,000 sheets A4 (3,000 sheets with BF-730 attachment); max. 60 – 300 g/m²; max. B5R – 305 x 457 mm Sub-tray: 200 sheets A4; 60 – 300 g/m²; A6R – 305 x 457 mm Sub-tray (top): 100 sheets; 60 – 300 g/m²; A6R – A4 Stapling up to 6c sheets A0 or 30 sheets A3 at 3 nocitions Stapling up to 65 sheets A4 or 30 sheets A3 at 3 positions,

B5 – 305 x 457 mm PH-7C/PH-7D Punch unit for DF-7110

2-hole/4-hole/Swedish type, 60 – 300 g/m², A5R – A3 MT-730(B) Mailbox sorter for DF-7110 7 bins x 100 sheets A4, 50 sheets A3/B4, 60 – 163 g/m² BF-730 Booklet and tri-folding unit for DF-7110

BI-730 Booklet and tri-lolding unit for DI-7110 Half folding: 60 – 256 g/m², A3, B4, A4R Booklet: max. 16 sheets (64 pages, 60 – 90 g/m²) Non-staple folding: max. 5 sheets (60 – 90 g/m²) Tri-folding: 60 – 105 g/m², A4R Multi tri-folding: 5 sheets (60 – 90 g/m²), 3 sheets (91 – 105 g/m²) Copy tray (D): upper tray 100 sheets, lower tray 250 sheets Banner Guide (A): Banner paper feeding guide, up to 10 sheets Security

Data Security Nit (E): In line with ISO 15408 (Common Criteria) with security level EAL2 USB IC Card Reader: Card Authentication Kit (B)

USB It. Card Reader: Card Authentication Rit (B)
Keybordholder 10
Numeric keypad: NK-7100
UG-33 AC: ThinPrint support
UG-34 AC: Emulation (IBM Proprinter/EPSON LQ-850)
Optional interface
IB-35: Direct Wi-Fi Interface

IB-50: Gigabit-Ethernet board 10BaseT/100BaseTX/1000BaseT IB-51: Wireless Lan Interface

















^{*} KYOCERA Document Solutions does not warrant that any specifications mentioned will be error-free. Specifications are subject to change without notice. Information is correct at time of going to press. All other brand and product names may be registered trademarks or trademarks of their respective holders and are hereby acknowledged.



^{**} Depending on the country